

Important

- The vanity must not be exposed to excessive moisture e.g. directly beside a bath or open shower. The materials used in the manufacture of Abby Bath vanities are water resistant **NOT WATER-PROOF**. If the installation is likely to encounter excessive moisture please consult your merchant for further advice.
- The warranty does not cover any costs associated with labour.
- Do not expose the vanity to solvents. Only use cleaning agents recommended for acrylics.
- Hire a professional contractor for installation.

Tools and Materials

Drill and drill bits Level Tape Measure Caulking gun
Lag Bolts (supplied) Screwdriver Pencil Silicone Sealant Cleaning materials

Wall Hung Vanity Installation

Important

Wall hung vanities MUST be installed into solid wood studs. Additional studs or nogs must be strategically located in the wall for proper installation. Failure to provide adequate support will void warranty.

1. Inspect that the unit is correct and undamaged. Please retain a copy of these instructions for reference purposes and warranty information.
2. Check all walls are plumb and straight
 - Cabinets installed on walls bowed in either the horizontal or vertical plane, may cause alignment and/or squareness issues, resulting in hardware malfunctioning.
3. Determine the height that vanity will be mounted at. This will depend on the required working height of vanity top surface and clearance requirements between tap ware and any mirrors above the vanity.
4. Place the cabinet into the proposed position (rest the cabinet on firm supports). Mark the positions of any plumbing outlets. Access to the cabinet can be made easily by the removal of the shelf, doors and/or drawers. Refer to "Removal & Alignment" section. When removing the fronts and shelves, ensure their positions are marked as they may not be interchangeable.
5. Reposition the cabinet back onto the supports. With a level check that the cabinet is leveled.

6. Using the 4 lag bolts provided, secure bolts through the plywood vanity back into studs. **If no solid wood studs are available, build a back support for proper vanity installation.**
7. Once the cabinet is in position the vanity top can be installed. Please refer to the Vanity Top installation section.

Vanity Top Installation

1. Clean the perimeter of the vanity and the underside of the top ensuring they are free of all debris.
2. Apply a small bead of neutral cure silicone (not supplied) to the four corners of the cabinet.
3. Place the vanity top into position

Removal and Alignment of Drawers

Removal

1. Make sure vanity is on flat surface and supported.
2. Pull the drawer towards you and lift up at 30-degree angle. For video guideline, please go to <https://www.youtube.com/watch?v=W19EbOQ9do0>

Alignment

1. Fully extend both sides.
2. Place drawer directly on the slides ensuring the slides are completely covered.
3. Close the drawer shut completely. (check the drawer has correctly engaged)

Date	Pack By: